

Specifications: Locktite Asbestos Encapsulant, Blue 5 gallon Pail, 55 gallon Drum

Appearance:	Milky Blue / Dries Blue
Odor:	Slight
Boiling Point:	>212°F
Vapor Density:	Heavier than air
pH:	7-8.5
Flash Point:	None
DOT Shipping Class:	55
Shipping Weight:	5 gal. pail 45lbs. 55 gal. drum 510lbs
Specific Gravity:	1.002
Solubility:	Dispersable
Reactivity:	Stable
HMS Rating:	1-0-0

DOT Shipping Name: COMBUSTIBLE LIQUID,
NOS (ESTERBLEND) COMBUSTIBLE LIQUID, NA
1993, PG II
DOT Hazard Label: NONE ON CONTAINERS
HAVE LESS THAN 110 GALLONS

**Twin-Chemicals
Atlanta, Georgia**

**(800) 442-4958
(770) 924-6147 fax**

www.twin-chemicals.com



PRONTO LOCKTITE is an economical and efficient asbestos lockdown encapsulant. This is a ready to use product that is designed to lock down asbestos fibers in your work areas and help you pass even the most aggressive air tests. **PRONTO LOCKTITE** penetrates asbestos rapidly and completely. When it penetrates, it absorbs onto the individual fibers to lock them together, reducing the possibility of loose fibers from becoming airborne during the removal process.

Directions:

1. Read and understand material safety data sheet when using this product.
2. Use full strength. Using an appropriate airless sprayer, mist all surfaces to lock down loose asbestos fibers on all fireproof insulation, protective barriers and ground/floor areas after any removal procedure.



TWIN CHEMICALS, INC.

(800) 442-4958 / (770) 924-6147 Fax
www.twin-chemicals.com
©2010 Twin Chemicals, Inc.



MATERIAL SAFETY DATA SHEET
PRONTO LOCKTITE - BLUE

MEETS REQUIREMENTS UNDER 29 CFR 1910.1200

PRODUCT IDENTIFICATION:

TRADE NAME: PRONTO LOCKTITE - BLUE
MANUFACTURED BY: TWIN-CHEMICALS
6175 Hickory Flat Hwy. Suite 110-344
Canton, GA 30115
CUSTOMER SERVICE PHONE: (800) 442-4958
EMERGENCY PHONE: (800) 552-3787
PREPARED BY: Cliff Cantrell
DATE PREPARED: July 12, 2009

COMPONENTS HAZARD INFORMATION:

OSHA PEL	ACGIH TLV	MAX% %W
----------	-----------	------------

CAS # *

Contains No Active Hazardous Materials.....

HMIS RATING: HEALTH: 1 FIRE: 0 REACTIVITY: 0 PERSONAL PROTECTION: A

PHYSICAL DATA:

BOILING POINT: >212 ° F SPECIFIC GRAVITY (WATER=1): 1.002
VAPOR PRESSURE (MM HG): ND MELTING POINT < 0 F
VAPOR DENSITY (AIR=1) ND EVAPORATION RATE (WATER=1): ND
APPEARANCE AND ODOR: Milky Blue with slight odor
SOLUBILITY IN WATER: DISPERSABLE pH: 7 to 8.5

FIRE AND EXPLOSION DATA:

FLASH POINT: none
FLAMMABLE LIMITS: NOT FLAMMABLE
EXTINGUISHING MEDIA: WATER FOG, CARBON DIOXIDE, DRY CHEMICAL, AND HALON.
SPECIAL FIRE FIGHTING PROCEDURES: NONE
UNUSUAL FIRE AND EXPLOSION HAZARDS: NONE

REACTIVITY DATA:

STABILITY: STABLE
INCOMPATIBILITY (MATERIALS TO AVOID) NONE
HAZARDOUS DECOMPOSITION OR BYPRODUCTS: NONE
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

HEALTH HAZARD DATA:

CARCINOGENICITY: NTP: NO IARC MONOGRAPHS: NO OSHA REGULATED: NO
ROUTE (S) OF ENTRY INHALATION? Not expected SKIN? YES EYES? YES INGESTION? YES
HEALTH HAZARDS (ACUTE AND CHRONIC) May cause irritation to eyes. Repeated use may lead to drying or reddening of skin.
SIGNS AND SYMPTOMS OF EXPOSURE:
INHALATION: NOT EXPECTED
INGESTION: MAY CAUSE IRRITATION TO THE ENTIRE GASTROINTESTINAL TRACT.
SKIN CONTACT: PROLONGED CONTACT MAY CAUSE IRRITATION TO SENSITIVE INDIVIDUALS.
EYE CONTACT: CONTACT MAY CAUSE IRRITATION.
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: NONE KNOWN

EMERGENCY AND FIRST AID PROCEDURES:

INGESTION: DRINK LOTS OF WATER TO DILUTE, INDUCE VOMITING BY STICKING FINGER DOWN THROAT. GET MEDICAL HELP.
INHALATION: MOVE VICTIM TO FRESH AIR. IF NECESSARY SUPPORT BREATHING. IF BREATHING DOES NOT RETURN TO NORMAL WITHIN A FEW MINUTES, GET MEDICAL ATTENTION.
EYE CONTACT: IMMEDIATELY FLUSH THE EYES FOR AT LEAST 15 MINUTES WITH LARGE AMOUNTS OF GENTLE, FLOWING WATER. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION.
SKIN CONTACT: FLUSH SKIN WITH WATER AND THEN WASH WITH SOAP AND WATER.

**MATERIAL SAFETY DATA SHEET
PRONTO LOCKTITE - BLUE**

PRECAUTIONS FOR SAFE HANDLING, USE, AND DISPOSAL:

SPILLS STOP SPILL AT SOURCE. FOR SMALL SPILLS FLUSH AWAY WITH WATER. FLOORS MAY BECOME SLIPPERY - AVOID FALL. FOR LARGE SPILLS, PUMP LIQUID INTO SALVAGE TANK, ABSORB WITH SAND, EARTH OR OTHER SUITABLE ABSORBENT. DISPOSAL MUST BE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

WASTE DISPOSAL: UNCONTAMINATED PRODUCT DOES NOT MEET RCRA DEFINITIONS OF HAZARDOUS CHECK LOCAL REGULATIONS BEFORE DISPOSAL.

HANDLING AND STORING: KEEP CONTAINER TIGHTLY CLOSED WHEN NOT IN USE.

AVOID CONTACT WITH SKIN AND EYES. STORE IN COOL, DRY AREA AWAY FROM SOURCES OF HEAT. WASHING WILL NOT MAKE CONTAINER SAFE FOR FOOD OR COSMETIC STORAGE.

SPECIAL PROTECTION AND CONTROL MEASURES:

RESPIRATORY PROTECTION: NA

VENTILATION: MECHANICAL WHEN USED IN ENCLOSED AREAS.

PROTECTIVE GLOVES: NA

EYE PROTECTION: NA

REPORTING REQUIREMENTS:

SARA TITLE III

REPORTING REQUIREMENTS

SECTION 302- EXTREME HAZARDOUS SUBSTANCES

NOT REQUIRED

SECTION 304- HAZARDOUS RELEASES

NOT REQUIRED

SECTION 311- COMMUNITY RIGHT TO KNOW (R-T-K)

NOT LISTED

SECTION 312- R-T-K INVENTORY DATA

NOT LISTED

SECTION 313- EMISSIONS AND RELEASE

NOT LISTED

CERCLA

THIS PRODUCT NOT REPORTABLE

THE INFORMATION CONTAINED HEREIN IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE SO. USERS ARE ADVISED TO CONFIRM IN ADVANCE OF NEED THAT INFORMATION IS CURRENT, APPLICABLE AND SUITED TO THE CIRCUMSTANCES OF USE. VENDOR ASSUMES NO RESPONSIBILITY FOR INJURY TO VENDEE OR THIRD PERSONS PROXIMATELY CAUSED BY THE MATERIAL IF REASONABLE SAFETY PROCEDURES ARE NOT ADHERED TO AS STIPULATED IN THE DATA SHEET. FURTHERMORE VENDOR ASSUMES NO RESPONSIBILITY FOR INJURY CAUSED BY ABNORMAL USE OF THIS MATERIAL EVEN IF REASONABLE SAFETY PROCEDURES IS FOLLOWED.