



*"Solving the environments problems with environmentally friendly solution"*

## PRONTO NO ODOR MASTIC REMOVER

PRONTO NO ODOR is a revolutionary new product. It is an extremely fast acting mastic remover. This product is perfect for those "sensitive jobs" that need to be done quickly.

### Specifications

Appearance	-----	Clear
Odor	-----	Low
Boiling Point	-----	>300
Vapor Density	-----	Heavier than Air
pH	-----	Neutral
Flash Point	-----	>178 F (TCC)
DOT Shipping Class	-----	55
Shipping Weight	5 gallon pail-----	35 lbs.
Shipping Weight	55 gallon drum-----	386 lbs.

### Application

Read and understand material safety data sheet when using this product. Apply manually or with garden sprayer to small areas, and take up material as quickly as possible to prevent excessive penetration into the substrate. Allow as little time as necessary to let PRONTO NO ODOR penetrate and soften the adhesive. Using a stiff bristled broom and/or squeegee, clean up liquefied mastic and dispose of properly. Be sure to not allow the mastic to come in contact with any areas which may absorb solvents such as sheetrock, woodwork, etc. or drains. Cover and dike these areas. Aggressively clean surface with water and detergent before applying new mastic.



6175 Hickory Flat Hwy. Suite 110-344 Canton, GA 30115  
(800) 442-4958 / (770) 924-6147 Fax  
[www.twin-chemicals.com](http://www.twin-chemicals.com)

**MATERIAL SAFETY DATA SHEET  
PRONTO NO ODOR MASTIC REMOVER**

MEETS REQUIREMENTS UNDER 29 CFR 1910.1200

**PRODUCT IDENTIFICATION:**

TRADE NAME:	PRONTO NO ODOR MASTIC REMOVER
SOLD BY:	TWIN-CHEM, INC. 6175 Hickory Flat Hwy. Suite 110-344 Canton, GA 30115 (800) 442-4958
CUSTOMER SERVICE PHONE:	(800) 552-3787
EMERGENCY PHONE:	(800) 552-3787
PREPARED BY:	CLIFFORD CANTRELL
DATE PREPARED:	JANUARY 26, 2004

**COMPONENTS HAZARD INFORMATION:**

	OSHA PEL	ACGIH TLV	OTHER MFG RECOMMENDED	MAX	CAS #
HYDROCARBON MIXTURE. T.S	NOT EST	NOT EST	100PPM	T.S.	
2-(2-BUTOXYETHOXY)-ETHANOL CAS # 112-34-5	NOT EST	NOT EST	< 15		

NOTE: AN \* UNDER 'SK' (SKIN) INDICATES THAT OSHA REQUIRE SKIN PROTECTION TO PREVENT OR REDUCE EXPOSURE TO THIS INGREDIENT. 2-(2-BUTOXYETHOXY) - ETHANOL IS A SARA TITLE III, SECTION 313 MATERIAL INGREDIENTS WHICH MAY BE SUBJECT TO REPORTING. T.S. - TRADE SECRET

HMIS RATING: HEALTH: 1 FIRE: 2 REACTIVITY: 0 PERSONAL PROTECTION: B

**PHYSICAL DATA:**

BOILING POINT:	400-420 F	SPECIFIC GRAVITY (WATER=1):	>0.790-0.805
VAPOR PRESSURE (MM HG):	< 1	MELTING POINT	< 30 F
VAPOR DENSITY (AIR=1)	5.8	EVAPORATION RATE (WATER=1):	< 1.0
APPEARANCE AND ODOR:	CLEAR LIQUID WITH FAINT BLAND ODOR		
SOLUBILITY IN WATER:	EMULSIFIABLE		
VOC CONTENT	635G/L 80%	5.30 LBS/GAL	

**FIRE AND EXPLOSION DATA:**

FLASH POINT: >178<sup>o</sup> F (TCC)  
FLAMMABLE LIMITS: NOT DETERMINED  
EXTINGUISHING MEDIA: WATER FOG, CARBON DIOXIDE, AND DRY CHEMICAL, FOAM. DO NOT USE DIRECT STREAM OF WATER. PRODUCT WILL FLOAT AND MAY REIGNITE ON WATER SURFACE.  
SPECIAL FIRE FIGHTING PROCEDURES: WEAR FULL PROTECTIVE CLOTHING AND SELF CONTAINED BREATHING APPARATUS TO PROTECT FROM POTENTIALLY TOXIC AND CORROSIVE FUMES UNDER FIRE CONDITIONS. THIS MATERIAL IS LIGHTER THAN WATER. USE OF WATER COULD RESULT IN SPREADING FIRE.  
UNUSUAL FIRE AND EXPLOSION HAZARDS: EMPTY AND PARTIALLY FILLED DRUMS MAY EXPLODE WHEN EXPOSED TO FIRE CONDITIONS.

**REACTIVITY DATA:**

STABILITY: STABLE  
INCOMPATIBILITY (MATERIALS TO AVOID): DO NOT MIX WITH OTHER CHEMICALS  
HAZARDOUS DECOMPOSITION OR BYPRODUCTS: HEAT, CARBON DIOXIDE. VARIOUS UNIDENTIFIED ORGANIC COMPOUNDS.  
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

**HEALTH HAZARD DATA:**

CARCINOGENICITY: NTP: NO IARC MONOGRAPHS: NO OSHA REGULATED: NO  
ROUTE (S) OF ENTRY INHALATION? YES SKIN? YES EYES? YES INGESTION? YES  
HEALTH HAZARDS (ACUTE AND CHRONIC) DIRECT EYE CONTACT MAY CAUSE REDNESS, BURNING SENSATION, DRYING AND CRACKING OF SKIN AND DERMATITIS. PERSONS WITH PREEXISTING SKIN DISORDERS MAY BE MORE SUSCEPTIBLE TO THESE EFFECTS.  
SIGNS AND SYMPTOMS OF EXPOSURE:  
INHALATION: PROLONGED OR EXCESSIVE EXPOSURE MAY RESULT IN CNS DEPRESSION, POSSIBLE DIFFICULTY IN BREATHING, DROWSINESS, AND ASTHMA LIKE SYMPTOMS.  
INGESTION: SMALL AMOUNTS MAY CAUSE EXTREME GASTRIC PAIN, DIARRHEA, VOMITING, DROWSINESS, DIZZINESS, FATIGUE, AND LOSS OF COORDINATION. IF LARGE QUANTITIES ARE INGESTED THE MATERIAL MAY BE ASPIRED TO THE LUNGS DURING SWALLOWING OR VOMITING.

**MATERIAL SAFETY DATA SHEET  
PRONTO NO ODOR MASTIC REMOVER**

---

**SKIN CONTACT:** PROLONGED CONTACT MAY CAUSE IRRITATION TO SENSITIVE INDIVIDUALS.

**EYE CONTACT:** CONTACT MAY CAUSE MINOR IRRITATION.

**MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:** PERSONS WITH PREEXISTING SKIN DISORDERS MAY BE MORE SUSCEPTIBLE EXPOSURE EFFECTS.

**EMERGENCY AND FIRST AID PROCEDURES:**

**INGESTION:** DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION IMMEDIATELY.

NOTE TO TREATING PHYSICIAN: SOLVENTS MAY BE ASPIRED INTO LUNGS.

**INHALATION:** MOVE VICTIM TO FRESH AIR. IF NECESSARY SUPPORT BREATHING. IF BREATHING DOES NOT RETURN TO NORMAL WITHIN A FEW MINUTES, GET MEDICAL ATTENTION.

**EYE CONTACT:** IMMEDIATELY FLUSH THE EYES FOR AT LEAST 15 MINUTES WITH LARGE AMOUNTS OF GENTLE, FLOWING WATER. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION.

**FLUSH SKIN WITH WATER AND THEN WASH WITH SOAP AND WATER**

**SKIN CONTACT:**

---

**PRECAUTIONS FOR SAFE HANDLING, USE, AND DISPOSAL:**

**SPILLS** \* EXTINGUISH ALL SOURCES OF IGNITION.

\* DIKE AREA AND ABSORB ON AN INERT ABSORBENT (SAND, VERMICULITE OR CLAY).

\* PLACE IN CHEMICAL CONTAINER FOR DISPOSAL

**WASTE DISPOSAL:** UNCONTAMINATED PRODUCT DOES NOT MEET RCRA DEFINITIONS OF HAZARDOUS (FLAMMABLE) WASTE. CHECK LOCAL REGULATIONS BEFORE DISPOSAL.

**HANDLING AND STORING:** KEEP CONTAINER TIGHTLY CLOSED WHEN NOT IN USE.

WARNING! EMPTIED CONTAINER RETAINS PRODUCT RESIDUE AND VAPORS. OBSERVE ALL PRECAUTIONS EVEN AFTER CONTAINER IS EMPTIED. WASHING WILL NOT MAKE CONTAINER SAFE FOR FOOD OR COSMETIC STORAGE.

KEEP THIS AND ALL CHEMICALS OUT OF REACH OF CHILDREN

---

**TRANSPORTATION:**

DOT 49 CFR 172.102

**DOT SHIPPING NAME:**

COMBUSTIBLE LIQUID, NOS (CONTAINS HYDROCARBON MIXTURE)

COMBUSTIBLE LIQUID, NA 1993, PG III

**DOT HAZARD LABEL:**

NONE ON CONTAINERS HAVE LESS THAN 110 GALLONS

---

**SPECIAL PROTECTION AND CONTROL MEASURES:**

**RESPIRATORY PROTECTION:** WHEN CONCENTRATIONS EXCEED ESTABLISHED EXPOSURE LIMITS USE NIOSH/MSMA APPROVED RESPIRATOR WITH ORGANIC VAPOR CARTRIDGE CCR-OV.

**VENTILATION:** MECHANICAL WHEN USED IN ENCLOSED AREAS.

**PROTECTIVE GLOVES:** RUBBER OR NEOPRENE.

**EYE PROTECTION:** CHEMICAL GOGGLES.

---

**REPORTING REQUIREMENTS:**

SECTION 302- EXTREMELY HAZARDOUS SUBSTANCES

SECTION 304- HAZARDOUS RELEASES

SECTION 311- COMMUNITY RIGHT TO KNOW (R-T-K)

SECTION 312- R-T-K INVENTORY DATA

SECTION 313- EMISSIONS AND RELEASE REPORTING MAY BE REQUIRED FOR USERS THE MANUFACTURING SECTOR.

CERCLA

SARA TITLE III

REPORTING REQUIREMENTS

NOT REQUIRED

NOT REQUIRED

REPORTING REQUIRED FOR INVENTORY ABOVE TPQ.

REPORTING REQUIRED FOR INVENTORY ABOVE TPQ.

SAME AS SECTION 304

---

THE INFORMATION CONTAINED HEREIN IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE SO. USERS ARE ADVISED TO CONFIRM IN ADVANCE OF NEED THAT INFORMATION IS CURRENT, APPLICABLE AND SUITED TO THE CIRCUMSTANCES OF USE. VENDOR ASSUMES NO RESPONSIBILITY FOR INJURY TO VENDEE OR THIRD PERSONS PROXIMATELY CAUSED BY THE MATERIAL IF REASONABLE SAFETY PROCEDURES ARE NOT ADHERED TO AS STIPULATED IN THE DATA SHEET. FURTHERMORE, VENDOR ASSUMES NO RESPONSIBILITY FOR INJURY CAUSED BY ABNORMAL USE OF THIS MATERIAL EVEN IF REASONABLE SAFETY PROCEDURES IS FOLLOWED.